







**Installation Instructions:**  
**JLT 2007-09 GT Fresh Air Kit (2005-09 Mustang GT, Shelby GT, California Special)**  
**#JLTFAK-FM05**

Thank you for purchasing our product. Take your time and it will be a smooth install.

**Please review complete instructions prior to installing.**

Step#	
1	<p><b>Verify you have all of the following parts included in the kit:</b> (1) Bracket, (1) 20" Section of Air Duct Hose, (1) 74" Section of Air Duct Hose, (2) 40 Hose Clamps, (6) Zip ties, (2) JLT Grille Bezels with Foam plugs</p>
2	<p><b>Gather all of the following tools needed for the installation:</b>  Tape measure, marker, 2 1/2" hole saw, angle drill or drill with extensions 5/16 Nut Driver, 10mm wrench or ratchet and socket, angle drill or drill with extensions</p>
3	<p>Raise car to good working height using lift or jack and jack stands.</p>
4	<p>Mark the center of your grille to be drilled. Measure 1.5" down from the top and 4 1/4" from the inside edge, this is your center. Mark the center of your grille to be drilled. Measure 1.5" down from the top and 4 1/4" from the inside edge, this is your center. Drill out the hole, then snap in the bezels.</p> <div style="display: flex; justify-content: space-around;">   </div>
5	<p>Using silver 10mm bolt on lower flange of drivers side headlight attach Fresh Air mounting bracket:</p> 

6	Starting with the drivers side, install 1 clamp on the end of the 20" air duct hose and clamp on to bezel and route up into the guide bracket installed in previous step.
7	Attach clamp to 74" air duct hose and clamp to passenger side bumper port as you did the drivers side.
8	Route hose along the front side of the radiator and A/C condenser and attach hose to the sway bar using supplied zip ties. Install hose in guide bracket with driver's side hose.
	



Thanks for the business. If you have any questions, please e-mail [Jay@JLTtruecoldair.com](mailto:Jay@JLTtruecoldair.com) or call 757-335-1940. Our hours are Monday-Friday, 8:00am – 5:00pm Eastern Time.

**Warranty:** JLT Performance Inc. will repair or replace any part of their product found upon our inspection to be defective in workmanship or material within 1 year from the purchase date for the original purchaser.

**Disclaimer:** JLT Performance Inc. makes no warranties whatsoever, expressed or implied, oral or written to any purchasers, except the warranty above. JLT Performance Inc. hereby specifically excludes from any implied warranty of merchantability or implied warranty of incidental, secondary, or consequential damages of any kind whatsoever. All purchasers and users of products manufactured by JLT Performance Inc. agree to hold harmless and indemnify JLT Performance Inc. from any and all claims arising from their use. Failure to receive notice of any or the limitations contained in this disclaimer shall not serve to extend liability to JLT Performance Inc. for any claims arising out of use of its products.

**Custom Paint Disclaimer:** All custom paint jobs are done by JLT Performance Inc. Every job is different and done by hand. By ordering a custom paint job, you accept this fact and cannot hold JLT Performance liable for the end result not being exactly what you had in your mind.

**Return Policy:** All returns will be subject to a 10%-25% restocking fee. Air Filters will not be accepted for return unless they are in original plastic sealed bag. Please visit [www.JLTtruecoldair.com](http://www.JLTtruecoldair.com) for complete return policy.